

DESCRIPTION

This wirelesss IOT Shock sensor starterkit includes everything you need to setup quickly your vibration monitoring application :

- Wireless Receiver/Gateway with LAN Output (Ref: BeanGateway® Indoor)
- Wireless accelerometer dedicated to shock measurement with integrated data logger. BeanDevice® 2.4GHz AX-3DS: ±2/4/8g
- 1 x Free software to collect and display in real-time data measurement (Ref: BeanScape[®] 2.4GHZ LITE)
- AC/DC Power Adapter (US or EUR or UK plugs) for charging the battery or to be used constantly

Date :28/04/2025

MAIN FEATURES

BeanAir

STARTER WIRELESS IOT SHOCK SENSOR

Wireless accelerometer dedicated to shock Scalable measurement range : ±2g/±4g/±8g

- 🕹 SSD (Smart Shock Detection), wireless sensor can wakeup on shock detection (software configurable)
- In the sector of the secto
- Time-synchronized data acquisition (±2.5ms of accuracy)
- 💮 Waterproof IP67 aluminum casing (Nema 6)
- Rechargeable Lithium-Polymer battery 2200 mAh providing a battery life up to 15 months
- Embedded data logger : up to 1 million data points (with events dating)
- Excellent radio link with a maximum range of 500 meters
- I x Free software to collect and display in real-time data measurement (Ref: BNSC-2.4GHZ-LITE)
- 1x Wireless Receiver/Gateway + Indoor Casing + LAN Output (Ref: BGTW-2.4GHZ-ETH-IND)
- AC/DC Power Adapter (US or EUR or UK plugs) for charging the battery or to be used constantly (ref: M8-PWR-12V)
 BeanAir[®] products are Made in Germany and are certified CE/FCC/Giteki, HS code: 9031.80.20

WEBLINKS TO PRODUCTS

- Wireless shock sensor
- Wireless Receiver/Gateway
- Eco-friendly Monitoring Software

HOW IT WORKS ?

BeanScape[®] 2.4GHz LITE Wireless IOT Supervision Software



BeanDevice[®] 2.4GHz AX-3DS Wireless IOT Shock Sensor

STARTERKIT WIRELESS IOT SHOCK SENSOR

DRAWING

BeanAir



